



Scratch-free

Industrial Scratch Resistant Coating



EN 12600 certified

International breakage certification



35 years of experience

One of the longest-operating distributors in the industry



Protection against shards of glass

In case of breakage, the glass is held together



Security adhesive

Considerably stronger than the adhesive of heat protection films



Protection against breakage

Getting through the glass is significantly slower



Crystal clear

The view is not distorted



Manufacturer

Avery Dennison Hanita Israel Ltd.



UV protection

Protects your health and your valuables

Level of protection



Protection against shards of glass

Protection against breakage

Safety with window films!

Tensile strength
32260 psi
222 N/mm²

Break strength
216 lbs/inch
38 N/mm

Puncture strength
149 lbs
663 N

	Single pane
Total Solar Energy Rejected	20%
Visible Light Transmitted	85%
Visible Light Reflected Exterior	10%
Total Solar Energy Reflected	10%
Total Solar Energy Absorbed	19%
Total Solar Energy Transmitted	71%
UV Rejection	99%
U-Value	5,96



Warranty

10 years



Certification

EN12600 1B1



Sizes available

0,91×30 m, 1,52×30 m,
1,82×30 m



Layers

One



Interior/exterior

Interior



Thickness

175 microns



Adhesive

Double security adhesive